



PASSENGER
ELEVATOR  FOUR
TECHNOLOGIES




► Intelligence - intelligent running, high-efficient experience

Intelligent group control manage system

By centralized control to multi elevators, this system will allocate elevator response rationally and dispatch the most suitable car to each landing. Ensure passengers to enjoy the timely service in any case.

Full computer intelligent control system

This system uses high-performance 64bit microcomputer processing chip, realizes multi – microcomputer, modularization, network control and improves data processing time. Intelligent microcomputer module built-in system combines fuzzy logic serial communication technology to achieve fast information transmission, improve the system scheduling and operation rate further, and make elevator performance more excellent.




► Comfort – enjoy smooth and pleasant trip

High-end door-motor system

The advanced VVVF control technology applies to the door-motor system, makes door starting, speeding up, braking curves smooth and fluent. Bring comfort to passengers by quiet switches.

Accurate position control system

This system uses advanced sensor that gets real-time signal feedback of the movement state of motor rotor. To make car positioning precision reach zero for better in and out freely.



PASSENGER ELEVATOR

FOUR TECHNOLOGIES

► Safety – humanity care all the way

ID/IC card identification system

This system controls the use of elevators by ID/IC card. Users take elevator by card to improve safety of buildings and efficiency of property management and create private space for them.

Infrared light curtain protection system

There's intensive light curtain protective barrier that naked eye cannot see at entrance, it could make sensitive response quickly to any objects in detection range in order to protect passenger safe efficiently.



► Energy-saving – green model, path to sustained

A new generation of gearless permanent magnet synchronous traction machine

Excellent driving performance, more high-efficient running smart figure with convenient layout saves 10% construction area compared with the same load gear elevator, it saves 50% electric energy.

Energy feedback technology

Through energy feedback device, electric energy converted by potential energy produced when in elevator running gives back to the grid for the use of other electrical equipments in the building, this device could save 30% electric energy efficiently.

LED energy-saving lighting in car

We adopt super long-life LED light without harmful substances to save 80% energy saving than conventional tube under the same illumination.

Car automatic lighting system

Turn off lighting automatically if nobody in the car.
Turn off lighting automatically after receiving calls.



PASSENGER ELEVATOR SMALL MACHINE ROOM



Less space, more intelligence

► Art everywhere – perfect overlap of machine room and shaft area

LARSSON passenger elevator with small machine room uses compact layout of gearless permanent magnet synchronous traction machine and control cabinet to save construction space and expand utility rate of space. As machine room area is exactly same with shaft area, a harmony mechanical and electrical greenway comes into being. It is perfect into the building and increasing the aesthetic feeling.



Leading advantage gives you unlimited possibility

► Optimize space, design span

With machine room less structure, control cabinet and traction are placed in the shaft flexibly. It saves construction area and with artistic and simple shape, which reduces comprehensive construction cost and leaves design space for architects and developers.



Traction machine top mounted



► Flexible layout, convenient maintenance

Traction machine is located between shaft top car and shaft wall, control cabinet is next to top hall door, which make the connection between them short enough, easy to repair and maintenance.

PASSENGER ELEVATOR WITHOUT MACHINE ROOM

Save construction area

Artistic and simple shape

Reduce comprehensive construction cost



PASSENGER ELEVATOR

STANDARD CAR DECORATION

► Car

► COP




Car walls with hairline stainless steel

► Ceiling

► Floor PVC

► Call



CL001



FR101



HB001



COP001

PASSENGER ELEVATOR

HOTEL
CAR DECORATION



» DC201

- Ceiling** Titanium mirror stainless steel
White organic board
- Car wall** Titanium mirror etching stainless steel
Titanium gold hairline stainless steel
- Floor** Standard PVC



» DC202

- Ceiling** Titanium gold stainless steel decorative strip
White organic board
- Car wall** Titanium mirror etching stainless steel
Titanium gold hairline stainless steel
- Handrail** Titanium mirror stainless steel
Wood veneer
- Floor** Standard PVC



» DC215

- Ceiling** Titanium mirror stainless steel
- Car wall** Titanium mirror etching stainless steel
Titanium gold hairline stainless steel
- Handrail** Titanium gold hairline stainless steel
- Floor** Standard PVC



» DC219

- Ceiling** Titanium mirror stainless steel
White organic board
- Car wall** Titanium mirror etching stainless steel
Titanium gold hairline etching stainless steel
- Handrail** Titanium mirror stainless steel
Wood veneer
- Floor** Standard PVC



» DC216

- Ceiling** Rose gold mirror etched stainless steel
Decorative lamp
- Car wall** Rose gold mirror etched stainless steel
Rose gold hairline stainless steel
- Handrail** Rose gold mirror stainless steel
- Floor** Standard PVC



» DC217

- Ceiling** Rose gold mirror etched stainless steel
White organic board; Downlights
- Car wall** Rose gold mirror etched stainless steel
Rose gold hairline stainless steel
- Floor** Standard PVC

PASSENGER
ELEVATOR BUSINESS
CAR DECORATION



» DC220

- Ceiling Mirror stainless steel
White organic board; Downlights
- Car wall Mirror etched stainless steel
Hairline stainless steel
- Handrail Hairline stainless steel
- Floor Standard PVC




» DC212

- Ceiling Mirror stainless steel; Downlights
- Car wall Mirror etched stainless steel
Hairline stainless steel
- Handrail Hairline stainless steel
- Floor Standard PVC (Optional : Marble)




» DC221

- Ceiling Hairline stainless steel; Downlights
- Car wall Mirror etched stainless steel
Hairline stainless steel
- Handrail Hairline stainless steel
- Floor Standard PVC (Optional : Marble)



» DC205

- Ceiling Mirror stainless steel decorative strip
White organic board
- Car wall Marble pattern board
Mirror stainless steel
- Floor Standard PVC (Optional : Marble)



» DC225

Ceiling	Black titanium mirror stainless steel White organic board; Downlights
Car wall	Mirror stainless steel Wood pattern board
Handrail	Black titanium gold hairline stainless steel
Floor	Standard PVC (Optional : Marble)



» DC227

Ceiling	Champagne gold mirror stainless steel White organic board ; Downlights
Car wall	Champagne gold mirror etched stainless steel Champagne gold hairline stainless steel
Handrail	Champagne gold mirror stainless steel
Floor	Standard PVC (Optional : Marble)



» DC226

Ceiling	Mirror stainless steel White light strip
Car wall	Wood pattern board Mirror stainless steel
Floor	Standard PVC (Optional : Marble)




» DC301

Ceiling	Hairline stainless steel White organic board ; Downlights
Car wall	Toughened glass Stainless steel baffle
Handrail	Hairline stainless steel
Floor	Standard PVC

PASSENGER ELEVATOR DECORATION SERIES

► PVC Floor



FR101



FR102



FR103



FR104




FR105



FR106




FR107



FR108


► Marble Floor(Optional)



FR001



FR002



FR003



FR004

► Ceiling



CL001



CL002




CL003



CL004




CL005



CL006



CL007



CL008



CL009

► Handrail



HR001



HR002



HR003



HR004



HR005




HR006



HR101



HR202



HR303



HR404

» **Door plank**
(Optional: Titanium gold; Rose gold; Champagne gold)



LD001



LD002




LD003



LD004




LD005



LD006



LD007



LD008




LD009



LD010

» **Spraying color**




RAL7035
(Standard)



RAL7037



RAL6027



RAL9001

» **Elevator multimedia information system**



Liquid crystal display
(Standard)



Liquid crystal display



Dot matrix display



Multimedia

» **COP**
(Split type)



COP001
(Standard)



COP002



COP004




COP003

» **COP**
(Integral type; Optional)

» **Barrier-free operating panel (Optional)**



COP501




COP502

» LOP



» Duplex LOP(Optional)


» Micro motion button



» Wall mount LOP(Optional)





» Hall direction lights (Optional)





» Transverse display (Optional)





Specifications of passenger elevator with machine room															
Load (kg)	Speed (m/s)	Car Size (mm)			Opening Size (mm)		Hoistway Size (mm)				Mzchine Room Size (mm)			HIGHEST Floors	Highest Rise Height (m)
		CW	CD	CH	OP	HH	HW	HD	OH	PIT	MRW	MRD	MRH		
450	1	1100	1100	2300	700	2100	1600	1700	4050	1400	1600	1700	≥2500	16	50
	1.5								4200	1500				25	75
630	1	1300	1200	2300	800	2100	1800	1800	4050	1400	1800	1800	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
800	1	1400	1350	2300	800	2100	1850	1950	4050	1400	1850	1950	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1000	1	1600	1500	2300	900	2100	2050	2100	4050	1400	2050	2100	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1150	1	1700	1500	2300	1000	2100	2200	2100	4050	1400	2200	2100	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1250	1	1700	1700	2300	1000	2100	2200	2400	4050	1400	2200	2400	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1350	1	1800	1700	2300	1100	2100	2400	2400	4050	1400	2400	2400	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1600	1	1900	1800	2300	1200	2100	2600	2500	4050	1400	2600	2500	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1								4050	1400				16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
	1														

Specifications of passenger elevator without machine room												
Load (kg)	Speed (m/s)	Car Size (mm)			Opening Size (mm)		Hoistway Size (mm)				HIGHEST Floors	Highest Rise Height (m)
		CW	CD	CH	OP	HH	HW	HD	OH	PIT		
450	1	1100	1100	2300	800	2100	1800	1450	4050	1300	16	50
	1.5								4200	1400	25	75
630	1	1200	1300	2300	800	2100	1950	1650	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90
800	1	1350	1400	2300	800	2100	2100	1800	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90
1000	1	1500	1600	2300	900	2100	2250	2000	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90
1150	1	1550	1700	2300	1000	2100	2400	2100	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90
1250	1	1700	1700	2300	1000	2100	2500	2100	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90
1350	1	1700	1800	2300	1100	2100	2500	2200	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90
1600	1	1800	1900	2300	1200	2100	2600	2300	4050	1300	16	50
	1.5								4200	1400	25	75
	1.75								4250	1450	30	90



Specification parameter of hospital elevator															
Load (kg)	Speed (m/s)	Car Size (mm)			Opening Size (mm)		Hoistway Size (mm)				Mzchine Room Size (mm)			HIGHEST Floors	Highest Rise Height (m)
		CW	CD	CH	OP	HH	HW	HD	OH	PIT	MRW	MRD	MRH		
1000	1	1100	2100	2300	800	2100	1900	2450	4050	1400	1900	2450	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1350	1	1300	2300	2300	1100	2100	2400	2700	4100	1450	2400	2700	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110
1600	1	1400	2400	2300	1200	2100	2600	2800	4100	1450	2600	2800	≥2500	16	50
	1.5								4200	1500				25	75
	1.75								4250	1550				30	90
	2								4400	1600				36	110

High speed passenger elevator															
Load (kg)	Speed (m/s)	Car Size (mm)			Opening Size (mm)		Hoistway Size (mm)				Mzchine Room Size (mm)			HIGHEST Floors	Highest Rise Height (m)
		CW	CD	CH	OP	HH	HW	HD	OH	PIT	MRW	MRD	MRH		
1050	3	1600	1500	2500	900	2300	2300	2500	5500	2800	2500	4600	≥2500	66	200
	3.5								5800	3350				66	200
	4								6100	4000				66	200
	4								6100	4000				66	200
1150	3	1700	1500	2500	1000	2300	2400	2500	5500	2800	2600	4600	≥2500	66	200
	3.5								5800	3350				66	200
	4								6100	4000				66	200
	4								6100	4000				66	200
1350	3	1800	1700	2500	1100	2300	2600	2700	5500	2800	2800	4600	≥2500	66	200
	3.5								5800	3350				66	200
	4								6100	4000				66	200
	4								6100	4000				66	200
1600	3	1900	1800	2500	1200	2300	2700	2800	5500	2800	2900	4600	≥2500	66	200
	3.5								5800	3350				66	200
	4								6100	4000				66	200
	5								7000	5000				66	200

PASSENGER ELEVATOR FUNCTION TABLE

Note: O is optional for residential △ is optional for business and hotel

General Protection

Closing time protection	Protection against reverse travel
Emergency fire operation (EFO)	Prevent slipping protection
Emergency lighting in the car	Safety circuit protection
Overload warning (Caution light and buzzer)	Limit protection
The screen door protection device	Upper and lower limit protection device
Car roof and control cabinet emergency electric operation	Door interlock protection
Fault automatic diagnosis	Operation contactor protection
Alarm bell	Brake detection and protection
Hitting the bottom buffer device	Manual brake release rescue (only for elevator with machine room)
Outside door zone without opening door	Machine room door switch
Wave detection of grid voltage	Driven equipment overheating protection (OHT)
Contactor feedback detection	Fire signal feedback
Relay detection protection	Electric brake (only for elevator without machine room)
Speed feedback detection	Power-off emergency leveling ○ △
Fault low-speed self-rescue	Emergency power supply device operation ○ △
HB button embedded self-diagnosis	Firefighters service (in car) ○ △

Information Display

Hall and car digital position indicator	Running number display
Hall and car call/register	Floor display character arbitrary setting
Hall and car running direction display	

Steady Running

Return to base station without call	End station for speed and floor number correction
Full collective control	Parking
Independent service	Two parallel △
Full-load direct running (LNS)	Door opening re-leveling ○
Automatic door switch	Advance door opening ○
Pre-torque output	Group control operation management ○ △
Upon elevator floor setting	Double-door elevator ○ △
Hoistway self-learning	

Comfortable Ride

Hall and car door setting time	Manually selected floor
Open and close button	Cancellation of wrong landing
Automatic ventilation and lighting of automatic control in car	Anti-nuisance operating
Automatic cancellation of reverse order	Car arrival gong △
HB calls door opening	Attendant control ○ △
Repeated closing door	Ventilator automatic control (only for residential) ○
Bypassed stop setting	Voice announcement ○
Input port evaluation	Liquid display (only for residential) ○

Security Monitoring

Intercom from monitor room to machine room, car (Exclude machine room wired to monitor room)	Card reader ○ △
	BA interface (Dry contact) ○ △
CCTV cable (From car to machine room) ○	Community monitoring panel ○ △
Elevator remote control	Community computer monitoring ○ △



Headquarters:

No. 168, Xiangcheng Avenue, Xiangcheng District,
Suzhou, Jiangsu, China 215151

E-Mail: info@elevators.cn

Tel: +86 512 6618 1118

<http://www.elevators.cn>

<http://www.facebook.com/larssonelevatorcn>

The brochure is only for your reference. Please refer to the respective technical documents, subject to change without notice.

LARSSON Elevator All Rights Reserved.

LARSSON 2023.01



PASSENGER ELEVATOR



LARSSON ELEVATOR CO.,LTD